

4-19-2013

MATERIAL SAFETY DATA SHEET

PL-200 Construction Adhesive

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE
MSDS Number: P71200145
Version Number 4
Revision Date: APR-07-2008
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: PL-200 (R) CONSTRUCTION ADHESIVE
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CORPORATION
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800) 321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class ADHESIVE
Trade Name PL Brands
Product Code _____

Other Names: DRYWALL CONSTRUCTION ADHESIVE

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
HEPTANE	142-82-5	10 - 15	Y
PETROLEUM NAPHTHA	64742-89-8	10 - 15	Y
XYLENE	1330-20-7	< 2.0	Y
Heavy Naphthenic Oil	64742-52-5	< 2.0	Y
SILICA, QUARTZ	14808-60-7	TRACE	Y

Ingredient Notes:

Remaining ingredients are not considered OSHA hazardous.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non-sag mastic
Appearance/Color: Tan
Solubility (in water): insoluble
pH Value, +/- .3: Not Applicable
Boiling Range: 180.°F - 270.°F (82.22°C - 132.22°C)

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE

MSDS Number: P71200145

Version Number 4

Revision Date: APR-07-2008

Page Number: 2

Vapor Pressure (mmHg): 29. @ 68.°F (20.°C)

Evaporation Rate: 2.8 times Faster than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight approx. 30.%

% Volatile, Volume approx. 45.%

Specific Gravity: 1.21489

VOC (less H₂O or exempt) 380 Gr/L (31%)

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES

Flammability Class 1B

Flash Point: 21.°F (-6.11°C)

Tag Closed Cup

Explosive Range (LEL/UEL): 1.%

6.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam

Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.

Solvent vapors are heavier than air and travel along the ground.

Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

PETROLEUM NAPHTHA LD50 5000. PPM

XYLENE LC50 6700. PPM
LD50 4.3 PPM
LD50 3.95 PPM

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE

MSDS Number: P71200145

Version Number 4

Revision Date: APR-07-2008

Page Number: 3

NTP? N/E | IARC Monographs? N/E | OSHA? NO

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.

Skin: Prolonged or repeated contact can cause moderate irritation, defatting, and dermatitis.

Inhalation: May cause nose or throat irritation. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention

Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.

Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

CHRONIC HAZARDS

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage or may cause cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.

Overexposure to XYLENE may cause injury to Liver, Kidney and blood.

SILICA: Normal use of this product does not produce dust. Sanding dried material could generate trace amounts of Silica (quartz) which is a suspect human carcinogen (IARC group 1).

Repeated and prolonged occupational overexposure to Crystalline Silica may cause silicosis, a progressively disabling lung disease.

SECTION VI - STABILITY AND REACTIVITY

Stability: Product is stable under normal storage conditions

Hazardous Polymerization: Will not occur under normal conditions

INCOMPATABILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE

MSDS Number: P71200145

Version Number 4

Revision Date: APR-07-2008

Page Number: 4

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas.

(Open windows and doors). Wear appropriate protective clothing.

Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
HEPTANE	400.00 PPM	N/est	N/est	500.00 PPM	400.00 PPM
PETROLEUM NAPHTHA	300.00 PPM	N/est	N/est	400.00 PPM	300.00 PPM
XYLENE	100.00 PPM	N/est	150.00 PPM	150.00 PPM	100.00 PPM
Heavy Naphthenic Oil	5.00 mg/M3	N/est	N/est	N/est	5.00 mg/M3
SILICA, QUARTZ	0.05 mg/F3	N/est	N/est	N/est	0.10 mg/M3

Note: The TLV for Silica is for the respirable fraction of dust only.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV.

Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely.

Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame.

Keep out of reach of children.

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE

MSDS Number: P71200145

Version Number 4

Revision Date: APR-07-2008

Page Number: 5

Keep container closed while not in use.

Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.

Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e.10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY

Classification: ORM-D

DOT Label Required: ORM-D

Shipping Document: CONSUMER COMMODITY, ORM-D

ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE

Classification: CLASS 3

DOT Label Required: Flammable Liquid, UN1133, Class 3

Shipping Document: ADHESIVE, 3, UN1133, PG III,
for 50 gal. drum use PG II

ERG Code: 128

AIR TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e.10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY

Classification: ORM-D

DOT Label Required: ORM-D-AIR

Shipping Document: Consumer Commodity, ORM-D

ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE

Classification: Class 3

DOT Label Required: Flammable Liquid, UN 1133, Class 3

Shipping Document: ADHESIVE, 3, UN1133, PG III,
for 50 gal. drum use PG II

ERG Code: 128

AIR TRANSPORT (IATA) - INTERNATIONAL

Units less than 5L (1.3 gallons liquid) i.e.10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE

MSDS Number: P71200145

Version Number 4

Revision Date: APR-07-2008

Page Number: 6

Classification: class 9

Label Required: ID8000

Shipping Document: Consumer Commodity, 9, ID8000

ERG Code: 9L

Units GREATER than 5L i.e. 5 Gal. pail, 50 gal. drum

Proper Shipping Name: ADHESIVE

Classification: Class 3

Label Required: Flammable Liquid, UN 1133, Class 3

Shipping Document: ADHESIVE, 3, UN1133, PGIII,
for 50 gal. drum use PG II

ERG Code: 3L

MARINE - OCEAN TRANSPORT (IMDG)

Units less than 5L (1.3 gallons liquid) i.e. 10oz, 28oz, 1 gal.

Proper Shipping Name: ADHESIVE

Classification: Class 3

Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on Ocean container only, not required on cartons)

Shipping Document: ADHESIVE, 3, UN1133, PG III, LTD.QTY.

EMS Code: F-E, S-D

Units GREATER than 5L i.e. 5 gal. pail, 50 gal. drum

Proper Shipping Name: ADHESIVE

Classification: Class 3

Label Required: Flammable Liquid, UN 1133, Class 3

Shipping Document: ADHESIVE, 3, UN1133, PGIII,
for 50 gal. drum use PG II

EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
XYLENE	1330-20-7	< 2.0

SARA Section 311/312 Hazard Categories met: Fire Hazard,
Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

DISCLAIMER:

The information contained herein is based on data available as of the

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-200 (R) CONSTRUCTION ADHESIVE

MSDS Number: P71200145

Version Number 4

Revision Date: APR-07-2008

Page Number: 7

date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.